



## NoteCart Unifit FV 30

Fixed shelves, Vertical


NoteCart Unifit FV 30 is a mobile storage and charging solution for 30 devices.

NoteCart UniFit is a mobile cabinet for storing and charging laptops, Chromebooks, tablets, iPads and similar devices.

Henning Larsen Architects are behind the Nordic-inspired aesthetic design of the NoteCart UniFit series, a design with rounded corners that will fit into any environment.

The four wheels on the NoteCart UniFit series have been developed to be extremely robust at the same time as they complement the rest of the design, so that the NoteCart is easy to roll - regardless of the weight of the many laptops/Chromebooks and the type of flooring under the mobile cabinet.

During operation, all electronic parts and power adapters are stored in the locked space behind the steel cabinet so that only the person in charge of IT has access to them. A secure cable management system ensures that the cables stay in the cabinet once they have been installed.



## NoteCart Unifit FV 30 Solutions

- Designed for vertical storing, charging and transporting up to 30 laptops, Chromebooks, tablets, iPads or similar devices.
- The cabinet is sturdy and easy to transport on its rubber wheels, which have been thoroughly tested. 2 wheels are equipped with brakes.
- Strong handles on the sides make it easy to push and move the steel cabinet.
- The cabinet has a cable system which ensures that the cables do not disappear and that they are stored clutter-free.
- The standard key locks on the front and rear doors mean that devices are stored safely. On demand locks can be mechanical or electronic code locks.
- The fan ensures that devices are charged without the temperature rising unnecessarily.
- The Unifit Series can be customized to include a Thermostat to program and control special ventilation periods on demand.
- The Unifit Series can be customized to include a Timer to program and control special charging periods on demand.
- The Unifit Series is equipped with an RJ45 contact as standard and on demand the can be customized to include a switch bracket on which you can mount your preferred switch which will ensure your cable access to all devices inside the NoteCart.

### DEVICES

Laptops, Chromebooks, tablets, iPads and similar devices

Designed for devices with a maximum thickness of 45 mm (see dimensions on page 3).

### OPTIONAL PURCHASES

NoteSecure - Item no. NC-O-SECURE

Mechanical combination lock -  
Item no. NC-O-CODE-MAN

Thermostat - Item no. NC-O-THERMO

Timer - Item no. NC-O-TIMER2

### ITEM NUMBER

NoteCart Unifit FV 30, Fixed shelves, Vertical  
Item no. NCU-32-FV-SC



1. Vertical storage, charging and transportation of up to 30 devices
2. Designated space behind the cart for storing power supplies, power panels and fan.
3. Key locks on the front and back doors are with different keys (2x2 keys included).
4. Sturdy handles, on/off switch and cable holder on the side.
5. High-quality wheels with ball bearings and proper rubber content. 2 wheels out of 4 are with brakes.

[leba-innovation.com](http://leba-innovation.com)



# NoteCart Unifit FV 30, Fixed shelves, Vertical

## Technical specifications

Part Number: NCU-30-FV-SC

<b>EXTERIOR DIMENSIONS</b>		<b>SHELF DIMENSIONS</b>	
Width (incl. handle)	625 (805) mm	3 shelves with 10 compartments	
Depth	625 mm	Width	45 mm (per compartment)
Height	1325 mm	Depth	390 mm
		Height	290 mm (per compartment)
<b>WEIGHT</b>	<b>89 kg</b>	<b>MAX. WEIGHT PER SHELF</b>	<b>25 kg</b>
<b>LOCKING SYSTEM</b>		<b>SHELF TECHNICAL COMPARTMENT, DIMENSIONS</b>	
Front door lock	3 point lock, 2 keys included	Width	295 mm
Back door lock	Standard key lock, 2 keys included	Depth	120 mm
		Height between shelves	115 mm
<b>CABLE MANAGEMENT</b>	<b>Yes</b>	<b>VENTILATION</b>	<b>Active fan, 36 dB with 2600 RPM CE/RoHS</b>
<b>CONNECTING CABLE</b>		<b>WHEELS EN-12532 CERTIFIED</b>	
Power connector output	C19, max. 16 AMP input	Material	Elastic rubber, strength 75 shore A
Cable length	1.8 m	Type	Ball bearing
		Capacity	150 kg per wheel
<b>CHARGING</b>	<b>AC</b>	Diameter	100 mm
<b>MAINTENANCE</b>		<b>ELECTRONICS</b>	
Recommended maintenance	Wipe with a damp cloth	Main power panel	Voltage: 230 VAC 50/60 Hz Current: 16 A/10 A, max 3680 W Connectors: 4 x C13 per connector with 3 sec. delay
<b>MATERIAL AND COLOUR</b>		Power panel	2 x 16 sockets: Voltage: 25 VAC 50/60 Hz. Current: 10 A, max 2500 W. 5A fuse per 4 sockets.
Cabinet/top	Stainless steel, black and grey powder coating		
<b>DISPOSAL</b>	<b>According to local standards</b>	<b>PACKAGING</b>	<b>Cardboard packaging, disposable. 100% recyclable</b>

### Certifications

Wheels: EN 12532 certified  
CE

### Guarantee

2 years on the electrical components, 5 years on the body

**leba-innovation.com**