



NoteCart Unifit 32 Laptops

Sliding shelves

NoteCart Unifit 32 is a mobile storage and charging solution for 32 laptops.

NoteCart UniFit is a mobile cabinet for storing and charging laptops, Chromebooks and similar devices on 16 sliding shelves.

Henning Larsen Architects are behind the Nordic-inspired aesthetic design of the NoteCart UniFit series, a design with rounded corners that will fit into any environment.

The four wheels on the NoteCart UniFit series have been developed to be extremely robust at the same time as they complement the rest of the design, so that the NoteCart is easy to roll - regardless of the weight of the many laptops/Chromebooks and the type of flooring under the mobile cabinet.

During operation, all electronic parts and power adapters are stored in the locked space behind the steel cabinet so that only the person in charge of IT has access to them. A secure cable management system ensures that the cables stay in the cabinet once they have been installed.



NoteCart Unifit 32 Laptops Solutions

- Designed with sliding shelves for storage, charging and transport of up to 32 laptops, Chromebooks or similar devices. To ensure the stability of the NoteCart, you can only pull out one shelf at a time.
- The cabinet is sturdy and easy to transport on its rubber wheels, which have been thoroughly tested. 2 wheels are equipped with brakes.
- Strong handles on the sides make it easy to push and move the steel cabinet.
- The cabinet has a cable system which ensures that the cables do not disappear and that they are stored clutter-free.
- The standard key locks on the front and rear doors mean that devices are stored safely. On demand locks can be mechanical or electronic code locks.
- The fan ensures that devices are charged without the temperature rising unnecessarily.
- The Unifit Series can be customized to include a Thermostat to program and control special ventilation periods on demand.
- The Unifit Series can be customized to include a Timer to program and control special charging periods on demand.
- The Unifit Series is equipped with an RJ45 contact as standard and on demand the can be customized to include a switch bracket on which you can mount your preferred switch which will ensure your cable access to all devices inside the NoteCart.

DEVICES

Laptops, Chromebooks and similar devices

Designed for devices with a maximum thickness of 55 mm (see dimensions on page 3).

OPTIONAL PURCHASES

NoteSecure - Item no. NC-O-SECURE

Mechanical combination lock -
Item no. NC-O-CODE-MAN

Thermostat - Item no. NC-O-THERMO

Timer - Item no. NC-O-TIMER2

ITEM NUMBER

NoteCart Unifit 32, Sliding shelves
Item no. NCU-32-SH-SC



1. Storage, charging and transportation of up to 32 laptops across 16 shelves with 2 devices on each shelf, on high-quality wheels with ball bearings.
2. Designated space behind the cart for storing power supplies, power panels and fan.
3. Sliding shelves installed where one shelf can be pulled out at the time.
4. Sturdy handles, on/off switch and cable holder on the side.
5. Key locks on the front and back doors are different (2x2 keys included).

leba-innovation.com

NoteCart Unifit 32 Laptops, Sliding shelves

Technical specifications

Part Number: NCU-32-SH-SC

EXTERIOR DIMENSIONS

Width (incl. handle)	870 (1050) mm
Depth	700 mm
Height	1355 mm

WEIGHT 130 kg

LOCKING SYSTEM

Front door lock	3 point lock, 2 keys included
Back door lock	Standard key lock, 2 keys included

CABLE MANAGEMENT Yes

CONNECTING CABLE

Power connector output	C19, max. 16 AMP input
Cable length	1.8 m

CHARGING AC

MAINTENANCE

Recommended maintenance Wipe with a damp cloth

MATERIAL AND COLOUR

Cabinet/top Stainless steel, black and grey powder coating

DISPOSAL According to local standards

SLIDING SHELF DIMENSIONS 16 shelves (2 units on each shelf)

Width	730 mm
Depth	420 mm
Height	55 mm

MAX. WEIGHT PER SHELF 25 kg

SHELF TECHNICAL COMPARTMENT, DIMENSIONS

Width	515 mm
Depth	120 mm
Height between shelves	115 mm

VENTILATION Active fan, 36 dB with 2600 RPM CE/RoHS

WHEELS EN-12532 CERTIFIED

Material	Elastic rubber, strength 75 shore A
Type	Ball bearing
Capacity	150 kg per wheel
Diameter	100 mm

ELECTRONICS

Main power panel	Voltage: 230 VAC 50/60 Hz Current: 16 A/10 A, max 3680 W Connectors: 4 x C13 per connector with 3 sec. delay
Power panel	32 sockets: Voltage: 25 VAC 50/60 Hz. Current: 10 A, max 2500 W. 5A fuse per 4 sockets. Number of groups: 4.

PACKAGING Cardboard packaging, disposable. 100% recyclable

Certifications

Wheels: EN 12532 certified
CE

Guarantee

2 years on the electrical components, 5 years on the body

leba-innovation.com